



EXFIL[®] BALLISTIC BOLTLESS H-BACK RETENTION SYSTEM

The EXFIL[®] Ballistic Boltless H-Back Retention System features hardware-free installation and adjustable space between the nape pad and helmet brim that accommodates long hair in a military-style bun.

- Front straps feature Cam Lock sliders for one-handed adjustment and secure fit; rear straps use pull-through ladder locks to maximize length adjustment
- Adjustment straps and chin cup designed for a close, comfortable fit to the wearer's face
- Asymmetric design keeps the buckle tucked smoothly along the jaw line while maintaining a snug, even feel around the chin cup
- Sheepskin leather chin cup lining ensures maximum comfort and chafe-free wear at any temperature
- Left eye dominant (LED) option also available



SIZING

HEAD CIRCUMFERENCE (IN/CM)	
Size 0 (S)	24-26 / 61-66
Size 1 (M/L)	26-29 / 66-74
Size 2 (XL)	27.5-32.5 / 70-82.5



WEIGHT

0.17 lbs (76 g)



COMPATIBILITY

- Compatible with EXFIL® Ballistic and EXFIL® Ballistic SL helmets

AVAILABLE COLORS



Ranger Green
(Pantone 7770c)

PART NUMBERS

- Ranger Green Size 0: 73-RET-H-50
- Ranger Green Size 0 LED: 73-RET-H-50-L
- Ranger Green Size 1: 73-RET-H-51
- Ranger Green Size 1 LED: 73-RET-H-51-L
- Ranger Green Size 2: 73-RET-H-52
- Ranger Green Size 2 LED: 73-RET-H-52-L





Featuring EXFIL® Rail 2.0



Featuring EXFIL® Rail 3.0



EXFIL® BALLISTIC

The EXFIL® Ballistic features a hybrid composite shell for increased strength with a unique geometry for optimal fit.

PERFORMANCE STANDARDS

- > NIJ III-A
- > 9mm BFD < 25.4 mm
- > DEF(AUST)10469
- > 17gr V50 > 731 m/s

ENVIRONMENTAL CONDITIONS / MIL-STD-810G METHODS

- > 501.5P1 High Temperature
- > 502.5P1 Low Temperature
- > 507.5 Humidity
- > 509.5 Salt Fog
- > 510.5P11 Blowing Sand/Dust
- > 514.6 Loose Cargo Vibration
- > 500.5P1 Low Pressure (Altitude)

WEIGHT

Complete system weight includes helmet shell, accessory rails, impact liner and retention system

- > Size 1 | Shell: 0.79 kg (1.75 lbs) | Complete System: 1.18 kg (2.6 lbs)
- > Size 2 | Shell: 0.84 kg (1.85 lbs) | Complete System: 1.25 kg (2.75 lbs)

SIZING

	SIZE 1	SIZE 2
Head Circumference (cm)	52-60	58-63
Head Circumference (in)	20.5-23.5	23-24.75
Hat Size (USA)	6 5/8-7 1/2	7 3/8-7 7/8
ACH/MICH Size Equivalent	S/M/L	L/XL



SHELL ASSEMBLY

- > Ballistic Performance: NIJ Level III-A (according to NIJ STD 0106.01/0108.01)
- > Fragment Performance: 17gr V50 \geq 731 m/s (2400 ft/s)
- > Backface Deformation: 9mm FMJ RN @ 425 m/s (1400 ft/s), BFD < 25.4 mm all locations
- > Ballistic Certification: Certified by a third-party NIJ accredited laboratory
- > High-cut shell with unique geometry for optimal fit
- > Wilcox® W shroud for NVG mounts, compatible with retractable lanyard system
- > EXFIL® Rail 2.0 System or EXFIL® Rail 3.0 System available

MATERIALS

- > Shell: Polyethylene and other fibers in a proprietary composite matrix
- > VELCRO® USA: Loop 1100, military loop
- > Hardware: Stainless steel with MIL-DTL-13924D black oxide coating
- > Side Accessory Rails: Glass-reinforced polycarbonate

LINER SYSTEM

- > Three-piece Zorbium® foam impact liner with 16 individual comfort pads in two thicknesses, all Berry compliant materials
- > Exceeds ACH Blunt Impact requirement per AR/PD10-02, 16Dec'13 – average below 70G across all impacts and temperatures

MATERIALS

- > Zorbium®: Proprietary polyurethane impact and comfort foam also used in the standard issue U.S. Army and Marine Corps 7-Pad System
- > Impact Liner: Proprietary water-resistant film and loop fabric covering
- > Comfort Pads: Proprietary water-resistant film and antimicrobial wicking fabric covering

RETENTION SYSTEM

- > Team Wendy® CAM FIT™ Retention with BOA® Fit System for optimized stability and fit
- > Features boltless design with high-strength hook/loop attachment, meets ACH pull strength requirements
- > Cam Lock sliders for one-handed adjustment and secure fit
- > Left eye dominant option available

MATERIALS

- > BOA® Fit System with micro-adjustable dial, coated stainless steel cable and low friction guides
- > MIL-DTL-32067 leather chin cup
- > 5/8" nylon webbing
- > Acetal buckles and cams
- > 500D Cordura nape pad with Zorbium® foam
- > Antimicrobial wicking headband sleeves

COLORS



Black (FED-STD-595C #37031)



Coyote Brown (FED-STD-595C #20150)



MultiCam® (Hydrographic)



Ranger Green (Pantone 7770c)

AVAILABLE ACCESSORIES

SHOCK CORD KIT INCLUDED

EXFIL® BALLISTIC HELMET COVERS

Mesh and nylon spandex cover available in Black, Coyote Brown, MultiCam®, MultiCam® Alpine, Ranger Green and Wolf Gray

EXFIL® BALLISTIC EAR COVERS

Extend ballistic coverage to greater than full-cut ACH

EXFIL® PELTOR™ HEADSET ADAPTERS

Provides direct rail mount of all Peltor™ ComTac™ systems (quick release optional for EXFIL® Rail 2.0; required for EXFIL® Rail 3.0)

EXFIL® QUICK RELEASE RAIL ADAPTERS

Tool-free accessory attachment, includes two 5-slot Picatinny rails

Full list of compatible accessories available on TeamWendy.com

SCAN / CLICK FOR
PART NUMBERS

